



# HFT 70RS

## Rigid Gooseneck Trailer

<b>NET CAPACITY</b>	70,000 lbs (31,750 kg)
<b>ESTIMATED WEIGHT</b>	19,000 lbs (8,618 kg)
<b>MAIN DECK LENGTH</b>	29' 5" (8.97 m)
<b>DECK WIDTH</b>	102" (2.59 m)



### STANDARD FEATURES

#### Winch:

- 12,000 lb (5,443 kg) hydraulic winch
- Winch protector
- Cable length - 60 ft (18.3 m)
- 1/2 in (12.7 mm) cable

#### Storage:

- Enclosed toolboxes located on both sides of gooseneck
- Weatherproof document storage box

#### Sub-frame:

- Air-ride suspension with dump valve
- High pressure hydraulic filter system
- LED running lights
- Rubber mounted sealed lights and harnesses
- Radial tires - 235/75R 17.5
- ABS braking system
- Auto slack adjusters
- Hub piloted disc wheels

#### Folding Tail:

- 6° break over angle
- Starburst decking
- 30,000 lb (13,607 kg) centered lift capacity
- Self cleaning bushings
- Adjustable loading dock height up to 60 in (1.52 m)
- Positive lock indicator lights
- Automatic tail lock system

#### Finish:

- Polyurethane primer and paint
- 1-5/8 in (41.28 mm) Knotless Apitong hardwood decking
- Flush mounted decking
- Rubber anti-spray and anti-sail mudflaps

### OPTIONS & ACCESSORIES

#### Options:

- 10 ft (3.05 m) hydraulic gooseneck ramp
- Dual side controls
- 20,000 lb (9,072 kg) hydraulic winch
- Disc brakes (includes 255/70R 22.5 tires)
- Two speed landing legs
- Polished aluminum wheels (set of 8, two sizes available)
- Air weigh system
- Canadian option

#### Accessories:

- Work around guiding winch system
- D-rings (outside of deck beams)
- Wireless remote (winch only)
- Wireless remote (hydraulic decks and winch)
- Hydraulic power unit - 20 hp Honda (This accessory replaces the passenger side gooseneck tool box)
- Tire inflation system (not available with disc brakes)
- Tire pressure visibility kit

RIGID GOOSENECK TRAILER  
HFT 70RS

# Rigid Gooseneck Trailer

## HFT 70RS

### Specifications

Trailer Measurements	
Overall length	48 ft (14.63 m)
Main deck length	29 ft 5 in (8.97 m)
Deck width	102 in (2.59 m)
Main deck height - loaded	35 1/2 in (90.2 cm)
Ground clearance - loaded	18 1/2 in (47 cm)
Net capacity - distributed	70,000 lbs (31,750 kg)
Net capacity - concentrated	50,000 lbs (22,680 kg) in 10 ft (3.04 m) concentration @ 60 mph (96.5 kph)
Stake pockets/key slots	48 in (122 cm) centers
Center deck key slots	48 in (122 cm) centers
Deck cross members	12 in (30.48 cm) centers
Tires	235/75R 17.5 16 ply
Axle capacity	22,500 lbs (10,205 kg)
Air brakes with ABS braking system	12 1/4 x 7 1/2 in (311 x 191 mm)
Estimated weight	19,000 lbs (8,618 kg)

Hydraulic Folding Tail Measurements	
Break over angle	6°
Lifting capacity	30,000 lbs (13,607 kg)
Adjustable loading height	Up to 60 in (1.52 m)
Overall length (Rear main platform & folding tail)	14 ft 6 in (4.42 m)
Rear main platform length	9 ft 6 in (2.9 m)
Folding tail length	5 ft (1.52 m)

Gooseneck Measurements	
Break over angle	10°
Gooseneck ramp length	10 ft (3.05 m)
Gooseneck deck length	9 ft (2.74 m)
Swing clearance	86 in (2.18 m)
Kingpin height	51 in (1.30 m)
Winch line pull	12,000 lbs (5,443 kg)
Winch cable length	60 ft (18.3 m) of 1/2 in (12.7 mm) cable

### Dimensions

